

IRIX/AXIS

コリメータ名	視野	最大エネルギー値 (Kev)5%透過	コリメータ分解能				システム感度 cpm/ μ Ci		備考
			0cm		10cm		9.5mm	19mm	
			9.5mm	19mm	9.5mm	19mm			
Dynamic	394x533	150	5.1	5.7	14.8	15.0	900	991	
General All Purpose	394x533	160	4.1	4.8	8.4	8.9	233	257	
High Resolution	394x533	160	3.9	4.7	7.0	7.6	161	177	
Ultra High Resolution	394x533	160	4.1	4.8	6.0	6.7	84	93	
High Resolution Fan Beam	394x383	160	3.8	4.3	5.6	5.7	185	224	
High Resolution Fan Beam	394x533	160	4.2		8.3		280		焦点距離 65cm
Ultra High Resolution Fan Beam	394x533	160	4.2		7.1		185		焦点距離 50cm
Medium Energy General Purpose	394x533	300	5.7	6.4	10.2	10.6	226	250	
High Energy	394x533	400	5.9	6.6	11.0	11.4	146	160	
Ultra High Energy	394x533	511	6.1	7.1	11.1	11.9	90	97	
Pinhole	145 Φ	400							
			5.1	5.7	6.4	6.8			アパーチャ 3mm
			6.8	7.3	9.3	9.6			アパーチャ 5mm
			8.8	9.2	12.5	12.8			アパーチャ 7mm